



VehiclePro Drying Aid RM 829 Classic

This drying aid quickly breaks down the water film and produces a long-lasting and protective layer. Also suitable for soft water and osmosis water. VDA-compliant.



Properties

- Effective drying aid for use in vehicle washing plants
- Can also be used as hot wax for vehicle protection
- Quick break down of the water film over a large surface area
- Excellent drying result
- Effective with all water hardness levels
- Particularly suitable with soft water or osmosis water
- Effectively protects for up to 1 month
- VDA-compliant
- NTA-free
- Free from mineral oils and mineral hydrocarbons

Application areas:

- Car dealership and garage: Cars
- Haulage contractors, bus operators: Commercial vehicle cleaning
- Commercial vehicle washes: Cars


Usage options

- Car washes

Container sizes

Container sizes	Part number
10 l	6.296-064.0
20 l	6.296-065.0
200 l	6.296-066.0

pH



Application:**Car washes**

- Insert the product into the system.
- Adjust dosage on the device.
- Start care programme.

Instructions for use:

- Avoid over-dosage.
- Use only on washed, well rinsed surfaces.
- Store away from frost.

Warnings and safety recommendations according to EC Directives:

- Warning
- H319 Causes serious eye irritation
- P264 Wash thoroughly after handling.
- P280i Wear eye/face protection.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313 If eye irritation persists: Get medical advice/attention.

Further information:

- VDA certification
- Material Safety Data Sheet (MSDS)

Dosage and yield:

Contents:	Cleaning method:	Primary mixture:	Dosage:	Soiling:	Yield:
1000 ml	Commercial vehicle washes		0.1-0.3 %		70 PKW

Please contact us for more information:

Alfred Kärcher SE & Co. KG

Alfred-Kärcher Straße 28-40
71364 Winnenden

Phone +49(0)7195-14-0
Fax +49(0)7195-14-2212

www.kaercher.com